(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 16 May 2002 (16.05.2002)

PCT

(10) International Publication Number WO 02/38418 A1

(51) International Patent Classification7:

B60R 19/02

- (21) International Application Number: PCT/SE01/02239
- (22) International Filing Date: 16 October 2001 (16.10.2001)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0004112-9

10 November 2000 (10.11.2000) S

- (71) Applicant (for all designated States except US): SSAB HARDTECH AB [SE/SE]; S-971 88 Luleå (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JONSSON, Martin [SE/SE]; Östra Järnvägsesplanaden 6, S-972 42 LUleå (SE). JUNTTI, Magnus [SE/SE]; Regnvägen 99, S-976 32 Luleå (SE).
- (74) Agent: ÅSLUND, Roland; SSAB Hardtech AB, S-971 88 Luleå (SE).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, Cl, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A BUMPER BEAM FOR A VEHICLE AND A METHOD OF ADAPTING A BUMPER BEAM TO VARIOUS VEHICLE MODELS



(57) Abstract: A bumper beam for a vehicle comprises a hat beam (10) with a cover (14). The hat beam has a crown (11) and side flanges (12, 13), and the cover (14) is fastened to the side flanges. The crown is fastened to the vehicle body. The cover (14) extends past at least one of the side flanges (12, 13) and it is stiffened by being transversely corrugated.



02/38418 A1

1

A bumper beam for a vehicle and a method of adapting a bumper beam to various vehicle models

Technical field

This invention relates to a bumper beam for a vehicle comprising a hat beam with a crown and side flanges, and a cover fastened to the side flanges, wherein the crown is fastened to the vehicle. The invention relates also to a method of adapting a bumper beam to various vehicle models built on the same platform when the ground clearance is not the same for all the models.

Background of the invention

The tests of bumpers are not standardised between USA and Europe and bumpers that cope with all the tests are heavy, big and expensive. In particular, in the pendulum tests, the pendulum does not hit at the same height in the USA test as in the European test. Some car models have therefore not the same bumper when sold in the USA as when sold in the EU. Various car and MPV models built on the same platform will have different ground clearance, that is, the platform will be at various heights. Therefore, various models built on the same platform usually have different bumper beams.

Object of invention and brief description of the invention

It is an object of invention to provide a bumper beam that is light in weight notwithstanding its large vertical extension. It is also an object to provide a bumper beam that can easily be adapted to vehicle models with different ground clearance and a method to adapt the bumper beam to such vehicles. To these ends, the cover of the bumper beam extends past at least one of the side flanges and has transverse stiffening means. The cover may be profiled transversely to provide for the stiffening means. One adapts the bumper beam to the various ground clearance by fastening the cover with different extension past at least one of the side flanges for different vehicle models. The invention is defined by the claims.

Brief description of the drawings

- Figure 1 is a top plan view of a bumper beam shown as an example of the invention.
- Figure 2 is a perspective view of the bumper beam shown in figure 1.
- Figures 3 and 4 are transverse sections taken along lines 3-3 and 4-4 respectively in figure 1.

Description of the illustrated and preferred embodiment of the invention.

The bumper beam shown in the figures comprises a hat beam 10 with a crown 11 and side flanges 12,13. A cover 14 is fastened to side flanges, suitably by being spot-welded thereto. The material in the hat beam and cover is formed sheet steel. Preferably, the material strength should be above 1200 N/mm² both in the cover and in the hat beam. The hat beam has its crown facing the vehicle and the crown is fastened to the vehicle body. When the bumper is the front bumper, the bumper beam can be fastened directly to the ends of the side rails of the vehicle platform or to crash boxes 15,16 fastened to the side rails as shown.

The cover 14 extends with a portion 17 past the lower flange 13 as shown in figures 3 and 4. In figure 1, the cover 14 is instead shown vertically centered on the hat beam 11. The cover is transversely profiled, preferably by being trapezoidally shaped, and this profiling makes the cover transversely stiff, that is, vertically stiff. Each individual trapezoidal profile can be considered as a stiffener. The extending flange portion 17 will be strong enough to withstand being hit by the pendulum in the pendulum test. Thus the cover 14 can be wide enough to be hit by the pendulum both in the US pendulum test and the European pendulum test although the hat beam need not be that wide and the bumper will be only marginally heavier than a corresponding bumper that copes with only one of the pendulum tests.

Since the cover 14 is spot-welded to the hat beam 11, its position in height of the cover 14 on the hat beam 11 can easily be adapted to variations in height of the platform above ground for variants of a vehicle model.


With the same hat beam 11 mounted on the side rails of a platform used for a car as well as for a MPV, the same cover 14 can be used both for the car and the MPV. For the car, the cover 14 can then for example be spot-welded to the hat beam 11 and extend above the hat beam whereas it can be spot-welded to extend below the hat beam for the MPV, which has its platform higher above the ground.


When there are big variation in ground clearance between vehicles built on the same platform, it might be necessary to use different covers 14, but such

In figures 1 and 2 is shown that the cover has portions 20,21 that are not corrugated. The portion 21 has a big hole through which a hook for towing may extend, which is fastened to the bottom of the hat beam. The cover 14 may have its transverse corrugation over its entire length.

Claims

- 1. A bumper beam for a vehicle comprising a hat beam (10) with a crown (11) and side flanges (12,13), and a cover (14) fastened to the side flanges, wherein the crown faces the vehicle and is fastened to the vehicle, characterised in that the cover (14) extends past at least one of the side flanges (12,13) and has transverse stiffening means.
- A bumper beam according to claim 1, characterised in that the transverse stiffening means comprise transverse corrugation of the cover (14).
- A method of adapting a bumper beam to various vehicle models built on the same platform when the ground clearance is not the same for all the models,
- 4. characterised in that a hat beam is used which is mounted to the platform with its crown and a cover wider than the hat beam is fastened to the side flanges of the hat beam and in that one adaptes the bumper beam to the various ground clearances of the various vehicle models by fastening the cover with different extension past at least one of the flanges for different models.





INTERNATIONAL SEARCH REPORT

International application No. PCT/SE 01/02239

3		101702 007			
A. CLASSIFICATION OF SUBJECT MATTER		·			
TPC7: R60R 19/02		tion and IPC			
IPC7: B60R 19/02 According to International Patent Classification (IPC) or to b	both national classifica	uon and n c			
B. FIELDS SEARCHED Minimum documentation searched (classification system follo	owed by classification s	ymbols)			
IPC7: B60R Documentation searched other than minimum documentation	n to the extent that su	ch documents are included in	the fields searched		
SE,DK,FI,NO classes as above	· · · · · · · · · · · · · · · · · · ·	nd where practicable, search	terms used)		
Electronic data base consulted during the international search	h (name of data base a	iid, where processor,			
		•			
EPO-INTERNAL, WPI DATA					
C. DOCUMENTS CONSIDERED TO BE RELEV	ANI		Relevant to claim No.		
Category* Citation of document, with indication, wh					
Y WO 9520506 A1 (PLANNJA HARD (03.08.95), page 6, lin	1,2				
			3		
A					
	1 2				
Y US 4088357 A (KLIE ET AL), column 4, line 20 - lin	1,2				
A					
	1-3				
A US 4765665 A (AKAHOSHI), 2					
		•			
·	·				
	·	J c	nex		
X Further documents are listed in the continuation	on of Box_C.	χ See patent family and			
Special categories of cited documents: "A" document defining the general state of the art which is no: of the art whi	4.4	er document published after the e and not in conflict with the ap- principle or theory underlying t	international filing date or priori plication but cited to understand the invention		
to be of particular relevance "E" earlier application or patent but published on or after the in	the claimed invention cannot be sidered to involve an inventive				
filing date "L" document which may throw doubts on priority claim(s) or to cited to establish the publication date of another clauton or	the claimed invention cannot be				
special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or	other co	nsidered to involve an investive	such documents, such combinati		
means "P" document published prior to the international filing date but	be	ing obvious to a person skilled i cument member of the same pa	Il tite air		
the priority date claimed Date of the actual completion of the international s		nailing of the internation			
Date of the actual completion of the international		1 9 -02- 20			
14 February 2002					
Name and mailing address of the ISA/	Authoriz	ed officer			
Swedish Patent Office Box 5055, S-102 42 STOCKHOLM		Nordström/JAn	na		
Facsimile No. +46 8 666 02 86	T'elephor	ne No. + 46 8 782 25 0			

INTERNATIONAL SEARCH REPORT Information on patent family members

28/01/02

International application No. PCT/SE 01/02239

Patent document cited in search report			Publication (Patent family member(s)		Publication date	
WO	9520506	A1	03/08/95	AU AU	1594095 A 6388294 A	15/08/95 11/10/94	
		٠,		BR	9406088 A	13/02/96	
				DE	19581488 T	02/01/97	
				DE	69413016 D	00/00/00	
	•			EP	0690746 A,B	10/01/96	
				GB	2301319 A,B	04/12/96	
			•	GB	9614522 D	00/00/00	
				SE	503450 C	17/06/96	
			•	SE	9400227 A	27/07/95	
		•	يثنث	US	5622105 A	22/04/97	
		. '· .	:	UŠ	5722708 A	03/03/98	
us	4088357	 А	09/05/78;	DE	2440708 A	04/03/76	
US	4765665	Α	23/08/88	NONE			
			30/03/00	ΛU	4578199 A	05/01/00	
WO	0017017	. V.T	30/03/00	UA	5722299 A	10/04/00	
		. •	*	BR	9913716 A	29/05/01	
		.*		EP	1113947 A	11/07/01	
			*	WO	9965455 A	23/12/99	
			29/04/99	 ЕР	1027231 A	16/08/00	
МО	9920490	A1	23/ U4/ 33 ::	SE	509041 C	30/11/98	
				SE	9703859 A	30/11/98	